

MID VOLTAGE CMC 1608 (0603) SERIES

Rated Voltage: 100V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMC 1608CG 2A100	*	10	D	0.8±0.10
CMC 1608CG 2A120	*	12	J, K	0.8±0.10
CMC 1608CG 2A150	*	15	J, K	0.8±0.10
CMC 1608CG 2A180	*	18	J, K	0.8±0.10
CMC 1608CG 2A220	*	22	J, K	0.8±0.10
CMC 1608CG 2A270	*	27	J, K	0.8±0.10
CMC 1608CG 2A330	*	33	J, K	0.8±0.10
CMC 1608CG 2A390	*	39	J, K	0.8±0.10
CMC 1608CG 2A470	*	47	J, K	0.8±0.10
CMC 1608CG 2A560	*	56	J, K	0.8±0.10
CMC 1608CG 2A680	*	68	J, K	0.8±0.10
CMC 1608CG 2A820	*	82	J, K	0.8±0.10
CMC 1608CG 2A101	*	100	J, K	0.8±0.10
CMC 1608CG 2A121	*	120	J, K	0.8±0.10
CMC 1608CG 2A151	*	150	J, K	0.8±0.10
CMC 1608CG 2A181	*	180	J, K	0.8±0.10
CMC 1608CG 2A221	*	220	J, K	0.8±0.10
CMC 1608CG 2A271	*	270	J, K	0.8±0.10
CMC 1608CG 2A331	*	330	J, K	0.8±0.10
CMC 1608CG 2A391	*	390	J, K	0.8±0.10
CMC 1608CG 2A471	*	470	J, K	0.8±0.10
CMC 1608CG 2A561	*	560	J, K	0.8±0.10
CMC 1608CG 2A681	*	680	J, K	0.8±0.10
CMC 1608CG 2A102	*	1000	J, K	0.8±0.10