

MID VOLTAGE CMC 2012 (0805) SERIES

Rated Voltage: 250V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMC 2012CG 2E100	*	10	D	0.6±0.10
CMC 2012CG 2E120	*	12	J, K	0.6±0.10
CMC 2012CG 2E150	*	15	J, K	0.6±0.10
CMC 2012CG 2E180	*	18	J, K	0.8±0.10
CMC 2012CG 2E220	*	22	J, K	0.8±0.10
CMC 2012CG 2E270	*	27	J, K	0.8±0.10
CMC 2012CG 2E330	*	33	J, K	0.8±0.10
CMC 2012CG 2E390	*	39	J, K	0.8±0.10
CMC 2012CG 2E470	*	47	J, K	0.8±0.10
CMC 2012CG 2E560	*	56	J, K	0.8±0.10
CMC 2012CG 2E680	*	68	J, K	0.8±0.10
CMC 2012CG 2E820	*	82	J, K	0.8±0.10
CMC 2012CG 2E101	*	100	J, K	0.8±0.10
CMC 2012CG 2E121	*	120	J, K	0.8±0.10
CMC 2012CG 2E151	*	150	J, K	0.8±0.10
CMC 2012CG 2E181	*	180	J, K	0.8±0.10
CMC 2012CG 2E221	*	220	J, K	0.8±0.10
CMC 2012CG 2E271	*	270	J, K	0.8±0.10
CMC 2012CG 2E331	*	330	J, K	0.8±0.10
CMC 2012CG 2E391	*	390	J, K	0.8±0.10
CMC 2012CG 2E471	*	470	J, K	1.0±0.15
CMC 2012CG 2E561	*	560	J, K	1.0±0.15
CMC 2012CG 2E681	*	680	J, K	1.0±0.15
CMC 2012CG 2E821	*	820	J, K	1.2±0.15
CMC 2012CG 2E102	*	1000	J, K	1.2±0.15