

## MID VOLTAGE CMK 1608 (0603) SERIES

**Rated Voltage: 100V**

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 1608XR 2A221	*	220	K, M	0.8±0.10
CMK 1608XR 2A271	*	270	K, M	0.8±0.10
CMK 1608XR 2A331	*	330	K, M	0.8±0.10
CMK 1608XR 2A391	*	390	K, M	0.8±0.10
CMK 1608XR 2A471	*	470	K, M	0.8±0.10
CMK 1608XR 2A561	*	560	K, M	0.8±0.10
CMK 1608XR 2A681	*	680	K, M	0.8±0.10
CMK 1608XR 2A821	*	820	K, M	0.8±0.10
CMK 1608XR 2A102	*	1000	K, M	0.8±0.10
CMK 1608XR 2A122	*	1200	K, M	0.8±0.10
CMK 1608XR 2A152	*	1500	K, M	0.8±0.10
CMK 1608XR 2A182	*	1800	K, M	0.8±0.10
CMK 1608XR 2A222	*	2200	K, M	0.8±0.10
CMK 1608XR 2A272	*	2700	K, M	0.8±0.10
CMK 1608XR 2A332	*	3300	K, M	0.8±0.10
CMK 1608XR 2A392	*	3900	K, M	0.8±0.10
CMK 1608XR 2A472	*	4700	K, M	0.8±0.10
CMK 1608XR 2A562	*	5600	K, M	0.8±0.10
CMK 1608XR 2A682	*	6800	K, M	0.8±0.10
CMK 1608XR 2A822	*	8200	K, M	0.8±0.10
CMK 1608XR 2A103	*	10000	K, M	0.8±0.10