

MID VOLTAGE CMK 1608 (0603) SERIES

Rated Voltage: 250V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 1608XR 2E221	*	220	K, M	0.8±0.10
CMK 1608XR 2E271	*	270	K, M	0.8±0.10
CMK 1608XR 2E331	*	330	K, M	0.8±0.10
CMK 1608XR 2E391	*	390	K, M	0.8±0.10
CMK 1608XR 2E471	*	470	K, M	0.8±0.10
CMK 1608XR 2E561	*	560	K, M	0.8±0.10
CMK 1608XR 2E681	*	680	K, M	0.8±0.10
CMK 1608XR 2E820	*	820	K, M	0.8±0.10
CMK 1608XR 2E102	*	1000	K, M	0.8±0.10
CMK 1608XR 2E122	*	1200	K, M	0.8±0.10
CMK 1608XR 2E152	*	1500	K, M	0.8±0.10
CMK 1608XR 2E182	*	1800	K, M	0.8±0.10
CMK 1608XR 2E222	*	2200	K, M	0.8±0.10
CMK 1608XR 2E272	*	2700	K, M	0.8±0.10
CMK 1608XR 2E332	*	3300	K, M	0.8±0.10
CMK 1608XR 2E392	*	3900	K, M	0.8±0.10
CMK 1608XR 2E472	*	4700	K, M	0.8±0.10