

MID VOLTAGE CMK 2012 (0805) SERIES

Rated Voltage: 100V

Part No.	Capacitance (PF)	Tolerance	Thickness (mm)
CMK 2012XR 2A221	*	220	K, M 0.6±0.10
CMK 2012XR 2A271	*	270	K, M 0.6±0.10
CMK 2012XR 2A331	*	330	K, M 0.8±0.10
CMK 2012XR 2A391	*	390	K, M 0.8±0.10
CMK 2012XR 2A471	*	470	K, M 0.8±0.10
CMK 2012XR 2A561	*	560	K, M 0.8±0.10
CMK 2012XR 2A681	*	680	K, M 0.8±0.10
CMK 2012XR 2A821	*	820	K, M 0.8±0.10
CMK 2012XR 2A102	*	1000	K, M 0.8±0.10
CMK 2012XR 2A122	*	1200	K, M 0.8±0.10
CMK 2012XR 2A152	*	1500	K, M 0.8±0.10
CMK 2012XR 2A182	*	1800	K, M 0.8±0.10
CMK 2012XR 2A222	*	2200	K, M 0.8±0.10
CMK 2012XR 2A272	*	2700	K, M 0.8±0.10
CMK 2012XR 2A332	*	3300	K, M 0.8±0.10
CMK 2012XR 2A392	*	3900	K, M 0.8±0.10
CMK 2012XR 2A472	*	4700	K, M 0.8±0.10
CMK 2012XR 2A562	*	5600	K, M 1.0±0.15
CMK 2012XR 2A682	*	6800	K, M 1.0±0.15
CMK 2012XR 2A822	*	8200	K, M 0.8±0.10
CMK 2012XR 2A103	*	10000	K, M 0.8±0.10
CMK 2012XR 2A123	*	12000	K, M 0.8±0.10
CMK 2012XR 2A153	*	15000	K, M 0.8±0.10
CMK 2012XR 2A183	*	18000	K, M 0.8±0.10
CMK 2012XR 2A223	*	22000	K, M 1.0±0.15
CMK 2012XR 2A273	*	27000	K, M 1.0±0.15
CMK 2012XR 2A333	*	33000	K, M 1.2±0.15
CMK 2012XR 2A473	*	47000	K, M 1.2±0.15