

MID VOLTAGE CMK 2012 (0805) SERIES

Rated Voltage: 500V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 2012CG 2H221	*	220	K, M	0.6±0.10
CMK 2012CG 2H271	*	270	K, M	0.6±0.10
CMK 2012CG 2H331	*	330	K, M	0.8±0.10
CMK 2012CG 2H391	*	390	K, M	0.8±0.10
CMK 2012CG 2H471	*	470	K, M	0.8±0.10
CMK 2012CG 2H561	*	560	K, M	0.8±0.10
CMK 2012CG 2H681	*	680	K, M	0.8±0.10
CMK 2012CG 2H821	*	820	K, M	0.8±0.10
CMK 2012CG 2H102	*	1000	K, M	0.8±0.10
CMK 2012CG 2H122	*	1200	K, M	0.8±0.10
CMK 2012CG 2H152	*	1500	K, M	1.0±0.15
CMK 2012CG 2H182	*	1800	K, M	1.0±0.15
CMK 2012CG 2H222	*	2200	K, M	1.2±0.15
CMK 2012CG 2H272	*	2700	K, M	1.2±0.15
CMK 2012CG 2H332	*	3300	K, M	1.2±0.15
CMK 2012CG 2H392	*	3900	K, M	1.2±0.15
CMK 2012CG 2H472	*	4700	K, M	1.2±0.15