

HIGH VOLTAGE CMK 3216 (1206) SERIES

Rated Voltage: 1KV

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 3216XR 3A101	*	100	K,M	0.8±0.10
CMK 3216XR 3A221	*	220	K,M	0.8±0.10
CMK 3216XR 3A271	*	270	K,M	0.8±0.10
CMK 3216XR 3A331	*	330	K,M	0.8±0.10
CMK 3216XR 3A391	*	390	K,M	0.8±0.10
CMK 3216XR 3A471	*	470	K,M	0.8±0.10
CMK 3216XR 3A561	*	560	K,M	0.8±0.10
CMK 3216XR 3A681	*	680	K,M	0.8±0.10
CMK 3216XR 3A821	*	820	K,M	0.8±0.10
CMK 3216XR 3A102	*	1000	K,M	0.8±0.10
CMK 3216XR 3A122	*	1200	K,M	0.8±0.10
CMK 3216XR 3A152	*	1500	K,M	1.2±0.15
CMK 3216XR 3A182	*	1800	K,M	1.2±0.15
CMK 3216XR 3A222	*	2200	K,M	1.2±0.15
CMK 3216XR 3A272	*	2700	K,M	1.2±0.15
CMK 3216XR 3A332	*	3300	K,M	1.2±0.15
CMK 3216XR 3A392	*	3900	K,M	1.2±0.15
CMK 3216XR 3A472	*	4700	K,M	1.2±0.15
CMK 3216XR 3A562	*	5600	K,M	1.2±0.15
CMK 3216XR 3A682	*	6800	K,M	1.2±0.15
CMK 3216XR 3A822	*	8200	K,M	1.2±0.15
CMK 3216XR 3A103	*	10000	K,M	1.2±0.15