

MID VOLTAGE CMK 3216 (1206) SERIES

Rated Voltage: 500V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 3216XR 2H221	*	220	K,M	0.8±0.10
CMK 3216XR 2H271	*	270	K,M	0.8±0.10
CMK 3216XR 2H331	*	330	K,M	0.8±0.10
CMK 3216XR 2H391	*	390	K,M	0.8±0.10
CMK 3216XR 2H471	*	470	K,M	0.8±0.10
CMK 3216XR 2H561	*	560	K,M	0.8±0.10
CMK 3216XR 2H681	*	680	K,M	0.8±0.10
CMK 3216XR 2H821	*	820	K,M	0.8±0.10
CMK 3216XR 2H102	*	1000	K,M	0.8±0.10
CMK 3216XR 2H122	*	1200	K,M	0.8±0.10
CMK 3216XR 2H152	*	1500	K,M	0.8±0.10
CMK 3216XR 2H182	*	1800	K,M	0.8±0.10
CMK 3216XR 2H222	*	2200	K,M	0.8±0.10
CMK 3216XR 2H272	*	2700	K,M	0.8±0.10
CMK 3216XR 2H332	*	3300	K,M	1.0±0.15
CMK 3216XR 2H392	*	3900	K,M	1.0±0.15
CMK 3216XR 2H472	*	4700	K,M	1.0±0.15
CMK 3216XR 2H562	*	5600	K,M	1.2±0.15
CMK 3216XR 2H682	*	6800	K,M	1.2±0.15
CMK 3216XR 2H822	*	8200	K,M	1.2±0.15
CMK 3216XR 2H103	*	10000	K,M	1.6±0.20
CMK 3216XR 2H123	*	12000	K,M	1.6±0.20
CMK 3216XR 2H153	*	15000	K,M	1.6±0.20
CMK 3216XR 2H183	*	18000	K,M	1.6±0.20