

## HIGH VOLTAGE CMK 4532 (1812) SERIES

**Rated Voltage: 2KV**

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 4532XR 3D101	*	100	K,M	1.2±0.15
CMK 4532XR 3D121	*	120	K,M	1.2±0.15
CMK 4532XR 3D151	*	150	K,M	1.2±0.15
CMK 4532XR 3D181	*	180	K,M	1.2±0.15
CMK 4532XR 3D221	*	220	K,M	1.2±0.15
CMK 4532XR 3D271	*	270	K,M	1.2±0.15
CMK 4532XR 3D331	*	330	K,M	1.2±0.15
CMK 4532XR 3D391	*	390	K,M	1.2±0.15
CMK 4532XR 3D471	*	470	K,M	1.2±0.15
CMK 4532XR 3D561	*	560	K,M	1.2±0.15
CMK 4532XR 3D681	*	680	K,M	1.2±0.15
CMK 4532XR 3D821	*	820	K,M	1.2±0.15
CMK 4532XR 3D102	*	1000	K,M	1.2±0.15
CMK 4532XR 3D122	*	1200	K,M	1.2±0.15
CMK 4532XR 3D152	*	1500	K,M	1.2±0.15
CMK 4532XR 3D182	*	1800	K,M	1.2±0.15
CMK 4532XR 3D222	*	2200	K,M	1.2±0.15
CMK 4532XR 3D272	*	2700	K,M	1.2±0.15
CMK 4532XR 3D332	*	3300	K,M	1.2±0.15
CMK 4532XR 3D392	*	3900	K,M	1.2±0.15
CMK 4532XR 3D472	*	4700	K,M	1.2±0.15