

HIGH VOLTAGE CMK 4532 (1812) SERIES**Rated Voltage: 3KV**

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 4532XR 3F101	*	100	K,M	1.6±0.20
CMK 4532XR 3F121	*	120	K,M	1.6±0.20
CMK 4532XR 3F151	*	150	K,M	1.6±0.20
CMK 4532XR 3F181	*	180	K,M	1.6±0.20
CMK 4532XR 3F221	*	220	K,M	1.6±0.20
CMK 4532XR 3F271	*	270	K,M	1.6±0.20
CMK 4532XR 3F331	*	330	K,M	1.6±0.20
CMK 4532XR 3F391	*	390	K,M	1.6±0.20
CMK 4532XR 3F471	*	470	K,M	1.6±0.20
CMK 4532XR 3F561	*	560	K,M	1.6±0.20
CMK 4532XR 3F681	*	680	K,M	1.6±0.20
CMK 4532XR 3F821	*	820	K,M	1.6±0.20
CMK 4532XR 3F102	*	1000	K,M	1.6±0.20
CMK 4532XR 3F152	*	1500	K,M	1.6±0.20
CMK 4532XR 3F182	*	1800	K,M	1.6±0.20
CMK 4532XR 3F222	*	2200	K,M	1.6±0.20