

MID VOLTAGE CMK 4532 (1812) SERIES

Rated Voltage: 500V

Part No.		Capacitance (PF)	Tolerance	Thickness (mm)
CMK 4532XR 2H472	*	4700	K,M	1.2±0.15
CMK 4532XR 2H562	*	5600	K,M	1.2±0.15
CMK 4532XR 2H682	*	6800	K,M	1.2±0.15
CMK 4532XR 2H822	*	8200	K,M	1.2±0.15
CMK 4532XR 2H103	*	10000	K,M	1.2±0.15
CMK 4532XR 2H123	*	12000	K,M	1.2±0.15
CMK 4532XR 2H153	*	15000	K,M	1.2±0.15
CMK 4532XR 2H183	*	18000	K,M	1.2±0.15
CMK 4532XR 2H223	*	22000	K,M	1.2±0.15
CMK 4532XR 2H273	*	27000	K,M	1.2±0.15
CMK 4532XR 2H333	*	33000	K,M	1.6±0.20
CMK 4532XR 2H393	*	39000	K,M	1.6±0.20
CMK 4532XR 2H473	*	47000	K,M	1.6±0.20
CMK 4532XR 2H563	*	56000	K,M	1.6±0.20
CMK 4532XR 2H683	*	68000	K,M	1.6±0.20
CMK 4532XR 2H823	*	82000	K,M	1.6±0.20